



Giuseppe Di Maria S.p.A.

BISATEN OPACA

Revision nr.1
Dated 20/07/2015
Printed on 11/04/2016
Page n. 1 / 9

Safety data sheet

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: 600105900010000
Product name: BISATEN OPACA

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: Anti-mold water-based paint, washable, with special aesthetic and protective characteristics.

1.3. Details of the supplier of the safety data sheet

Name: Giuseppe Di Maria S.p.A.
Full address: Via Enrico Mattei, 4
District and Country: 90124 Palermo (PA)
Italia
Tel. 091 391288
Fax 091 476374

e-mail address of the competent person responsible for the Safety Data Sheet: sicurezza@dimaria.it

Product distribution by: Giuseppe Di Maria S.p.A.

1.4. Emergency telephone number

For urgent inquiries refer to:

Phone numbers of Poison Control Centers active 24 hours over 24 in Italy:
TORINO: Centro Antiveleni - Azienda Ospedaliera "S.G. Battista"
- Molinette di Torino - Tel. 011 6637637
MILANO: Centro Antiveleni - Ospedale Niguarda Ca' Granda - Tel. 02 66101029
PAVIA: Cen. Naz. Inform. Tossic. Fond. S. Maugeri
- Clinica del Lavoro e della Riabilitazione - Tel. 0382 24444
PADOVA: Serv. Antiv. - Cen. Interdipartiment. di Ricerca sulle Intossicaz. Acute
- Dip. di Farmac. E. Meneghetti - Università degli Studi di Padova - Tel. 049 8275078
GENOVA: Servizio Antiveleni - Serv. Pr. Socc., Accett. e Oss.
- Istituto Scientifico G. Gaslini - Tel. 010 5636245
FIRENZE: Centro Antiveleni - U.O. Tossicologia Medica
- Azienda Ospedaliera Careggi - Tel. 055 4277238
ROMA: Centro Antiveleni - Policlinico A. Gemelli
- Università Cattolica Del Sacro Cuore - Tel. 06 3054343
ROMA: Centro Antiveleni - Istituto Di Anestesiologia e Rianimazione
- Università Degli Studi Di Roma La Sapienza - Tel. 06 49970698
NAPOLI: Centro Antiveleni - Azienda Ospedaliera A. Cardarelli - Tel. 081 7472870

For more information: Giuseppe Di Maria SpA Tel. 091 391288
Monday to Friday 9:00-12:00 13:00-17:00

SECTION 2. Hazards identification.

2.1. Classification of the substance or mixture.

The product is classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Hazardous to the aquatic environment, chronic toxicity, H412 Harmful to aquatic life with long lasting effects.
category 3

2.2. Label elements.

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.



Giuseppe Di Maria S.p.A.

BISATEN OPACA

Revision nr.1
Dated 20/07/2015
Printed on 11/04/2016
Page n. 2 / 9

SECTION 2. Hazards identification. ... / >>

Hazard pictograms: --

Signal words: --

Hazard statements:

H412

EUH210

EUH208

Harmful to aquatic life with long lasting effects.

Safety data sheet available on request.

Contains:

Miscela di: 5-cloro-2-metil-2H-isotiazol-3-one [EC no. 247-500-7],

2-metil-2H-isotiazol-3-one [EC no. 220-239-6] 3:1)

4,5-dicloro-2-ottil-2H-isotiazol-3-one

2-octyl-2H-isothiazol-3-one

May produce an allergic reaction.

Precautionary statements:

P273

P501

Avoid release to the environment.

Dispose of contents / container collection points for hazardous or special waste

2.3. Other hazards.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients.

3.1. Substances.

Information not relevant.

3.2. Mixtures.

Contains:

Identification.

Conc. %.

Classification 1272/2008 (CLP).

ETHANEDIOL

CAS. 107-21-1

0,25 - 0,3

Acute Tox. 4 H302, STOT RE 2 H373

EC. 203-473-3

INDEX. 603-027-00-1

Piridin-1-ossi-2titolo, sali di zinco

CAS. 13463-41-7

0,15 - 0,2

Acute Tox. 3 H301, Acute Tox. 3 H331, Eye Dam. 1 H318, Skin Irrit. 2 H315,
Aquatic Acute 1 H400 M=10

EC. 236-671-3

INDEX.

2-octyl-2H-isothiazol-3-one

CAS. 26530-20-1

0 - 0,05

Acute Tox. 3 H311, Acute Tox. 3 H331, Acute Tox. 4 H302, Skin Corr. 1B H314, Skin Sens. 1 H317,
Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410, EUH208

EC. 247-761-7

INDEX. 613-112-00-5

4,5-dicloro-2-ottil-2H-isotiazol-3-one

CAS. 64359-81-5

0 - 0,025

Acute Tox. 4 H302, Acute Tox. 4 H312, Skin Corr. 1B H314, STOT SE 3 H335, Skin Sens. 1 H317,
Aquatic Acute 1 H400 M=100, Aquatic Chronic 1 H410, EUH208

EC. 264-843-8

INDEX.

Note: Upper limit is not included into the range.

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures.

4.1. Description of first aid measures.

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.



Giuseppe Di Maria S.p.A.

BISATEN OPACA

Revision nr.1
Dated 20/07/2015
Printed on 11/04/2016
Page n. 3 / 9

SECTION 4. First aid measures. ... / >>

4.2. Most important symptoms and effects, both acute and delayed.

For symptoms and effects caused by the contained substances, see chap. 11.

4.3. Indication of any immediate medical attention and special treatment needed.

Information not available.

SECTION 5. Firefighting measures.

5.1. Extinguishing media.

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide and chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water.

Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture.

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

If large quantities of the product are involved in a fire, they can make it considerably worse. Do not breathe combustion products.

5.3. Advice for firefighters.

GENERAL INFORMATION

In the case of fire, use jets of water to cool the containers to prevent the risk of explosions (product decomposition and excess pressure) and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Remove all containers containing the product from the fire, if it is safe to do so.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures.

6.1. Personal precautions, protective equipment and emergency procedures.

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions.

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up.

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Check incompatibility for container material in section 7. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage.

7.1. Precautions for safe handling.

Ensure that there is an adequate earthing system for the equipment and personnel. Avoid contact with eyes and skin. Do not breathe powders, vapours or mists. Do not eat, drink or smoke during use. Wash hands after use. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities.

Store only in the original container. Store in a ventilated and dry place, far away from sources of ignition. Keep containers well sealed. Keep the product in clearly labelled containers. Avoid overheating. Avoid violent blows. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s).

Information not available.



SECTION 8. Exposure controls/personal protection.

8.1. Control parameters.

Regulatory References:

FRA	France	JORF n°0109 du 10 mai 2012 page 8773 texte n° 102
GRB	United Kingdom	EH40/2005 Workplace exposure limits
IRL	Éire	Code of Practice Chemical Agent Regulations 2011
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
EU	OEL EU	Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC.
	TLV-ACGIH	ACGIH 2014

ETHANEDIOL

Threshold Limit Value.

Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
VLEP	FRA	52	20	104	40	SKIN.
WEL	GRB	52	20	104	40	
OEL	IRL	52	20	104	40	SKIN.
TLV	ITA	52	20	104	40	SKIN.
OEL	EU	52	20	104	40	SKIN.
TLV-ACGIH				100 (C)		

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must be CE marked, showing that it complies with applicable standards.

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type B filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS.

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

SECTION 9. Physical and chemical properties.

9.1. Information on basic physical and chemical properties.

Appearance	liquid
Colour	white
Odour	Not available.
Odour threshold.	Not available.
pH.	7,5
Melting point / freezing point.	Not available.
Initial boiling point.	Not available.
Boiling range.	Not available.



Giuseppe Di Maria S.p.A.

BISATEN OPACA

Revision nr.1
Dated 20/07/2015
Printed on 11/04/2016
Page n. 5 / 9

SECTION 9. Physical and chemical properties. ... / >>

Flash point.	> 60 °C.
Evaporation Rate	Not available.
Flammability of solids and gases	Not available.
Lower inflammability limit.	Not available.
Upper inflammability limit.	Not available.
Lower explosive limit.	Not available.
Upper explosive limit.	Not available.
Vapour pressure.	Not available.
Vapour density	Not available.
Relative density.	1,29 Kg/l
Solubility	Not available.
Partition coefficient: n-octanol/water	Not available.
Auto-ignition temperature.	Not available.
Decomposition temperature.	Not available.
Viscosity	7500 ± 10000 cps
Explosive properties	Not available.
Oxidising properties	Not available.
9.2. Other information.	
Solid content.	55,70 %

SECTION 10. Stability and reactivity.

10.1. Reactivity.

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions.

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4. Conditions to avoid.

None in particular. However the usual precautions used for chemical products should be respected.

10.5. Incompatible materials.

Information not available.

10.6. Hazardous decomposition products.

Information not available.

SECTION 11. Toxicological information.

11.1. Information on toxicological effects.

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

This product contains sensitizing substance/s and may cause allergic reactions.

Piridin-1-ossi-2titolo, sali di zinco

LD50 (Oral).	269 mg/kg Rat
LD50 (Dermal).	> 2000 mg/kg Rat
LC50 (Inhalation).	0,6 mg/l Rat

2-octyl-2H-isothiazol-3-one

LD50 (Oral).	550 mg/kg ratto
LD50 (Dermal).	690 mg/kg coniglio

ETHANEDIOL

LD50 (Oral).	> 2000 mg/kg Rat
LD50 (Dermal).	9530 mg/kg Rabbit



SECTION 12. Ecological information.

This product is dangerous for the environment and the aquatic organisms. In the long term, it have negative effects on aquatic environment.

12.1. Toxicity.

Piridin-1-ossi-2titolo, sali di zinco	
LC50 - for Fish.	0,021 mg/l/96h <i>Lepomis macrochirus</i>
EC50 - for Crustacea.	0,05 mg/l/48h <i>Daphnia magna</i>
EC50 - for Algae / Aquatic Plants.	0,067 mg/l/72h <i>Selenastrum capricornutum</i>

4,5-dicloro-2-ottil-2H-isotiazol-3-one	
LC50 - for Fish.	0,0027 mg/l/96h <i>Oncorhynchus mykiss</i>
EC50 - for Crustacea.	0,0052 mg/l/48h <i>Daphnia magna</i>

2-octyl-2H-isothiazol-3-one	
LC50 - for Fish.	0,14 mg/l/96h <i>Pimephales promelas</i>
EC50 - for Crustacea.	0,18 mg/l/48h <i>Daphnia magna</i>

12.2. Persistence and degradability.

ETHANEDIOL	
Solubility in water.	mg/l 1000 - 10000
Rapidly biodegradable.	

12.3. Bioaccumulative potential.

ETHANEDIOL	
Partition coefficient: n-octanol/water.	-1,36

12.4. Mobility in soil.

Information not available.

12.5. Results of PBT and vPvB assessment.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects.

Information not available.

SECTION 13. Disposal considerations.

13.1. Waste treatment methods.

Reuse, when possible. Neat product residues should be considered special non-hazardous waste.
Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.
CONTAMINATED PACKAGING
Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information.

14.1. UN number.

Not applicable.

14.2. UN proper shipping name.

Not applicable.

14.3. Transport hazard class(es).

Not applicable.

14.4. Packing group.

Not applicable.



Giuseppe Di Maria S.p.A.

BISATEN OPACA

Revision nr.1
Dated 20/07/2015
Printed on 11/04/2016
Page n. 7 / 9

SECTION 14. Transport information. ... / >>

14.5. Environmental hazards.

Not applicable.

14.6. Special precautions for user.

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code.

Information not relevant.

SECTION 15. Regulatory information.

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.

Seveso category. None.

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006.

Product.

Point. 3

Substances in Candidate List (Art. 59 REACH).

None.

Substances subject to authorisation (Annex XIV REACH).

None.

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None.

Substances subject to the Rotterdam Convention:

None.

Substances subject to the Stockholm Convention:

None.

Healthcare controls.

Information not available.

VOC (Directive 2004/42/EC) :

Matt coatings for interior walls and ceilings.

VOC given in g/litre of product in a ready-to-use condition :

Limit value: 30,00 (2010)

VOC content limit : 30,00

- Thinned by weight with : 11,00 % ACQUA

15.2. Chemical safety assessment.

No chemical safety assessment has been processed for the mixture and the substances it contains.

SECTION 16. Other information.

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Acute Tox. 3	Acute toxicity, category 3
Acute Tox. 4	Acute toxicity, category 4
STOT RE 2	Specific target organ toxicity - repeated exposure, category 2
Skin Corr. 1B	Skin corrosion, category 1B
Eye Dam. 1	Serious eye damage, category 1
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Skin Sens. 1	Skin sensitization, category 1
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic toxicity, category 1
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
H301	Toxic if swallowed.
H311	Toxic in contact with skin.
H331	Toxic if inhaled.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.



Giuseppe Di Maria S.p.A.

BISATEN OPACA

Revision nr.1
Dated 20/07/2015
Printed on 11/04/2016
Page n. 8 / 9

SECTION 16. Other information. ... / >>

H373	May cause damage to organs through prolonged or repeated exposure.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H317	May cause an allergic skin reaction.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH208	Contains <name of sensitising substance>. May produce an allergic reaction.
EUH210	Safety data sheet available on request.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EU) 1907/2006 (REACH) of the European Parliament
 2. Regulation (EU) 1272/2008 (CLP) of the European Parliament
 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
 4. Regulation (EU) 2015/830 of the European Parliament
 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- The Merck Index. - 10th Edition
 - Handling Chemical Safety
 - INRS - Fiche Toxicologique (toxicological sheet)
 - Patty - Industrial Hygiene and Toxicology
 - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
 - ECHA website

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.
This document must not be regarded as a guarantee on any specific product property.



Giuseppe Di Maria S.p.A.

BISATEN OPACA

Revision nr.1

Dated 20/07/2015

Printed on 11/04/2016

Page n. 9 / 9

SECTION 16. Other information. ... / >>

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.
Provide appointed staff with adequate training on how to use chemical products.